



AS5013-00 / AS5014-00

ADDRESSABLE DUCT SENSORS



Standard Features

- Detects and limits the spread of smoke throughout building HVAC ducts
- Compatible with building automation and fire alarm systems
- Installs quickly and easily
- No screens or filters to clean
- Rugged gray steel back box with clear cover
- Accessories - Remote LED alarm indication capability
- Meets UL 268A Requirements



Application

The Avenger AS5013 and AS5014 Analog Photoelectric Duct Smoke Sensor provides early detection of smoke and products of combustion present in air moving through HVAC ducts in Commercial, Industrial and Residential applications.

The Analog Photoelectric Duct Smoke Sensor is designed to prevent the recirculation of smoke in areas by the air handling systems, fans and blowers. Complete systems may be shut down in the event of smoke detection.

The Avenger AS5013 and AS5014 operate on a DCP powered loop (24 VDC source required for AS5014).

Operation

The AS5013 and AS5014 are designed and built to meet all local requirements, as well as the NFPA regulations regarding duct smoke sensors.

Output terminals are provided for remote accessories such as a horn, strobe, remote status indicators and reset key switches or push buttons. Air sampling is accomplished by two tubes which protrude into the duct. An exhaust tube of one standard length (7.5") is supplied in the installation kit with the smoke duct unit. Once the duct width has been determined the air intake sampling tubes must be ordered. Sampling tubes are supplied in three standard lengths 2.5 ft., 5 ft. and 10 ft. and cut to size to fit the duct.

Mounting the duct smoke unit is accomplished by the use of a template and 4 sheet metal screws, which are provided. Mounting can be achieved without the removal of the clear cover which is secured by 4 capture screws.

The compact AS5014 contains 2 sets of form "C" contacts rated at 10 amps.

The pilot and alarm visual indicators, provided on the front of the AS5014 duct unit, signal the operating status of the device. A manual test/ reset switch is located alongside the visual indicators.

After addressing, Analog Duct Sensors are fully configurable through Loop Explorer Software.



Engineering Specification

The Dealer shall furnish and install where indicated on the plans, the Avenger Systems AS5013 or AS5014 Analog Photoelectric Duct Sensors.

The modules shall be UL listed compatible with Avenger Systems Digital Communications Protocol (DCP) supporting Supreme control panel loops. The sensors shall be listed by Underwriters Laboratories per UL 268A.

The sensors shall operate at air velocities from 300 feet per minute to 4,000 feet per minute. The duct detector housings shall be of metal construction and complete mechanical installation may be performed without removal of detector cover. The duct sensor shall not require additional filters or screens which must be maintained. The housing shall contain a base which will accept an analog photoelectric sensor head. Terminal connections shall be of the screw type and be a minimum of #6 screw. For installations requiring relay function, terminals shall be provided for remote pilot, remote alarm indication, strobe / horn and remote key switch. For installation not requiring relay function, visual indication of alarm and power must be provided on detector front.

A manual reset switch shall be located on front of the device. All wiring must comply with local codes and regulations.

State-of-the-art communications protocol, DCP, allows multiple system component types to be used concurrently in a system's Signaling Line Circuit.

Technical Specifications

Model #	AS5013-00	AS5014-00
Average Current Consumption (on S-SC Line)	2mA	10mA
Sensor Type	Addressable Photoelectric	Addressable Photoelectric
Input Voltage	DCP Powered Loop	DCP Powered Loop / AUX 24VDC
Sensitivity Test Method	Control Panel	Control Panel
Contacts	N/A	2 form C rated 10A @ 250VAC
Standby Current	390µA	390µA
Alarm Current	540µA	540µA
Operating Temperature Range	32°F - 100°F	32°F - 100°F
Relative Humidity	10-85%, non-condensing	10-85%, non-condensing
Air Velocity	300 to 4000 ft/min	300 to 4000 ft/min
Sampling Tubes	2.5ft., 5ft., 10ft.	2.5ft., 5ft., 10ft.
Housing	18 G.A. steel backbox, clear plastic cover	18 G.A. steel backbox, clear plastic cover
Dimensions	9 1/8"(L) x 7 1/4"(W) x 2 1/4"(D)	9 1/8"(L) x 7 1/4"(W) x 2 1/4"(D)
Weight	3lbs.	3lbs.
Finish	Gray Paint	Gray Paint
Remote Indication	Alarm	Alarm / Pilot